



Specifications



SUPER STRADDLE MODELS		AWP™-20S		AWP™-25S	
MEASUREMENTS	Metric	US	Metric	US	
A Height	1.78 m	5 ft 10 in	1.78 m	5 ft 10 in	
B Length (adjustable)	2.77 - 3.25 m	9 ft 1 in - 10 ft 8 in	2.77 - 3.25 m	9 ft 1 in - 10 ft 8 in	
C Width	.97 m	3 ft 2 in	.97 m	3 ft 2 in	
Width with required outriggers	1.75 m	5 ft 9 in	2.05 m	6 ft 9 in	
D Wheelbase (adjustable)	2.64 - 3.25 m	8 ft 8 in - 10 ft 8 in	2.64 - 3.25 m	8 ft 8 in - 10 ft 8 in	
E Straddle clearance	1.22 m	4 ft	1.22 m	4 ft	
F Height to ladder	.69 m	2 ft 3 in	.69 m	2 ft 3 in	
G Height to fixed wheel	1.02 m	3 ft 4 in	1.02 m	3 ft 4 in	
Storage dimensions (l/w/d)	2.03/0.94/0.61 m	80/37/24 in	2.03/0.94/0.61 m	80/37/24 in	
WEIGHT					
	263 kg	580 lbs	263 kg	580 lbs	

SUPER STRADDLE MODELS		AWP™-30S		AWP™-36S	
MEASUREMENTS	Metric	US	Metric	US	
A Height	1.78 m	5 ft 10 in	1.78 m	5 ft 10 in	
B Length (adjustable)	2.77 - 3.25 m	9 ft 1 in - 10 ft 8 in	2.77 - 3.25 m	9 ft 1 in - 10 ft 8 in	
C Width	.97 m	3 ft 2 in	.97 m	3 ft 2 in	
Width with required outriggers	2.31 m	7 ft 7 in	2.57 m	8 ft 5 in	
D Wheelbase (adjustable)	2.64 - 3.25 m	8 ft 8 in - 10 ft 8 in	2.64 - 3.25 m	8 ft 8 in - 10 ft 8 in	
E Straddle clearance	1.22 m	4 ft	1.22 m	4 ft	
F Height to ladder	.69 m	2 ft 3 in	.69 m	2 ft 3 in	
G Height to fixed wheel	1.02 m	3 ft 4 in	1.02 m	3 ft 4 in	
Storage dimensions (l/w/d)	2.03/0.94/0.61 m	80/37/24 in	2.03/0.94/0.61 m	80/37/24 in	
WEIGHT					
	263 kg	580 lbs	263 kg	580 lbs	

SUPER STRADDLE MODELS		AWP™-40S	
MEASUREMENTS	Metric	US	
A Height	1.78 m	5 ft 10 in	
B Length (adjustable)	2.77 - 3.25 m	9 ft 1 in - 10 ft 8 in	
C Width	.97 m	3 ft 2 in	
Width with required outriggers	2.77 m	9 ft 1 in	
D Wheelbase (adjustable)	2.64 - 3.25 m	8 ft 8 in - 10 ft 8 in	
E Straddle clearance	1.22 m	4 ft	
F Height to ladder	.69 m	2 ft 3 in	
G Height to fixed wheel	1.02 m	3 ft 4 in	
Storage dimensions (l/w/d)	2.03/0.94/0.61 m	80/37/24 in	
WEIGHT			
	263 kg	580 lbs	

UK

The Maltings
Wharf Road
Grantham NG31 6BH
UK
Tel: +44 (0)1476 584333
Fax: +44 (0)1476 584334

France

10, ZA de la Croix St. Mathieu
28320 Gallardon
France
Tel: +33 (0)2 37 26 09 99
Fax: +33 (0)2 37 26 09 98

Germany

Finienweg 3
28832 Achim/Bremen
Germany
Tel: +49 (0)4202 8852-0
Fax: +49 (0)4202 8852-25

Spain

Gaià 31, Pol. Ind. Plá d'en Coll
08110 Montcada i Reixac
Barcelona
Spain
Tel: +34 93 572 50 90
Fax: +34 93 572 50 91

Scandinavia

Aröds industriväg 34
422 43 Hisings Backa
Sweden
Tel: +46 31 57 51 00
Fax: +46 31 57 51 04

Middle East

Terex Middle East
PO Box 282325, Dubai
U.A.E.
Tel: +971 4 885 8030
Fax: +971 4 885 6364
Email: awp.infome@terex.com

Genie United States

18340 NE 76th Street
P.O. Box 97030
Redmond, WA
USA 98073-9730
Tel: +1 425 881-1800
Fax: +1 425 883-3475

Email: AWP-InfoEurope@terex.com

Distributed By:

Features

EASILY CONFIGURED TO MEET YOUR NEEDS

PLATFORM OPTIONS

- Sliding mid-rail standard platform
- Gated standard platform
- Gated narrow platform
- Standard fibreglass platform

POWER OPTIONS

- AC power 85 V / 50-60 Hz
- AC power 110 V / 50-60 Hz
- AC power 220 V / 50-60 Hz
- DC 12V with 110 V / 230 V / 50-60 Hz with worldwide automatic “smart” charging system
- Air motor power 1.5 hp (1.1 kW) (AWP™-30 only)

BASE OPTIONS

- Standard base
- Rough terrain (RT) base (AWP™-20, -25, 30 only)

OPTIONS & ACCESSORIES

PRODUCTIVITY

- Gated standard platform
- Gated narrow platform
- Standard fibreglass platform
- Tilt-back frame (option on AWP™-20, -25, -30 only)
- Operational warning light and descent alarm package
- Tool tray
- Fluorescent tube caddy
- Platform locating laser light

POWER

- Air motor power 1.5 hp (1.1 kW) (AWP™-30 only)



Standard Base

STANDARD FEATURES

MEASUREMENTS

AWP™-20S

- 8.12 m (26 ft 1 in) working height
- 6.12 m (20 ft 1 in) platform height
- 74 cm (2 ft 5 in) standard base width
- 76 cm (2 ft 6 in) RT base width
- Up to 159 kg (350 lb) lift capacity

AWP™-25S

- 9.56 m (31 ft 36 in) working height
- 7.56 m (24 ft 80 in) platform height
- 74 cm (2 ft 5 in) standard base width
- 76 cm (2 ft 6 in) RT base width
- Up to 159 kg (350 lb) lift capacity

AWP™-30S

- 11 m (35 ft 6 in) working height
- 9 m (29 ft 6 in) platform height
- 74 cm (2 ft 5 in) standard base width
- 76 cm (2 ft 6 in) RT base width
- Up to 159 kg (350 lb) lift capacity

AWP™-36S

- 13.10 m (42 ft 5 in) working height
- 11.10 m (36 ft 5 in) platform height
- 74 cm (2 ft 5 in) standard base width
- Up to 159 kg (350 lb) lift capacity

AWP™-40S

- 14.28 m (46 ft 85 in) working height
- 12.28 m (40 ft 29 in) platform height
- 74 cm (2 ft 5 in) standard base width
- Up to 136 kg (300 lb) lift capacity

PRODUCTIVITY

- Auxiliary platform lowering
- Most rigid mast in the industry
- Rocker base system for manoeuvrability
- Tilt base frame (standard on AWP™-36, -40)
- Easily rolls through standard doorways
- AC power to platform
- Dual activated up/down switch
- Small outrigger footprints
- Outrigger storage pockets
- Easy loading in pickup trucks
- Tie down attachment points
- Overhead crane attachment point
- Wide forklift pockets
- Rear access forklift pocket
- LED lights confirm proper set-up
- Certified load sensor

POWER

- AC power 85V / 50-60 Hz
- AC power 110V / 50-60 Hz
- AC power 220V / 50-60 Hz
- DC power 110V / 230V / 50-60 Hz with worldwide automatic “smart” charging system



**Sales
 Rental
 Service**

HELI.be

Vantegemstraat 9 | B-9230 Wetteren | +32 9 368 80 80 | info@heli.be

Specifications

MODELS	AWP™-20S		AWP™-25S		AWP™-30S	
MEASUREMENTS	Metric	US	Metric	US	Metric	US
Working height*	8.12 m	26 ft 1 in	9.56 m	31 ft 36 in	11 m	35 ft 6 in
Platform height	6.12 m	20 ft 1 in	7.56 m	24 ft 80 in	9 m	29 ft 6 in
A Height - stowed (Standard)	1.98 m	6 ft 6 in	1.98 m	6 ft 6 in	1.98 m	6 ft 6 in
stowed (RT)	2.01 m	6 ft 7 in	2.01 m	6 ft 7 in	2.01 m	6 ft 7 in
B tilted back** (Standard)	1.78 m	5 ft 10 in	1.84 m	6 ft .3 in	1.89 m	6 ft 2.5 in
C Length - stowed (Standard)	1.24 m	4 ft 1 in	1.31 m	4 ft 3.5 in	1.35 m	4 ft 5 in
stowed (RT)	1.60 m	5 ft 3 in	1.60 m	5 ft 3 in	1.60 m	5 ft 3 in
D Length - tilted back**	2.11 m	6 ft 11 in	2.11 m	6 ft 11 in	2.11 m	6 ft 11 in
E Width (Standard)	74 cm	2 ft 5 in	74 cm	2 ft 5 in	74 cm	2 ft 5 in
Width (RT)	76 cm	2 ft 6 in	76 cm	2 ft 6 in	76 cm	2 ft 6 in

PRODUCTIVITY						
Lift capacity	159 kg	350 lbs	159 kg	350 lbs	159 kg	350 lbs
Indoor:						
F G Outrigger footprint (l/w) (Standard)	1.55 m/1.35 m	5 ft 1 in/4 ft 5 in	1.75 m/1.55 m	5 ft 9 in/5 ft 1 in	1.93 m/1.73 m	6 ft 4 in/5 ft 8 in
Outrigger footprint (l/w) (RT)	1.63 m/1.27 m	5 ft 4 in/4 ft 2 in	1.63 m/1.27 m	5 ft 4 in/4 ft 2 in	1.83 m/1.52 m	6 ft/5 ft
H Corner access*** (Standard)	38 cm	1 ft 3 in	48 cm	1 ft 7 in	56 cm	1 ft 10 in
Corner access*** (RT)	53 cm	1 ft 9 in	51 cm	1 ft 8 in	70 cm	2 ft 3.5 in
I J Wall access front/side (Standard)	15 cm/33 cm	6 in/1 ft 1 in	18 cm/43 cm	7 in/1 ft 5 in	20 cm/53 cm	8 in/1 ft 9 in
Wall access front/side (RT)	30 cm/43 cm	1 ft/1 ft 5 in	25 cm/43 cm	10 in/1 ft 5 in	23 cm/51 cm	9 in/1 ft 8 in
Outdoor:						
F G Outrigger footprint (l/w) (Standard)	2.46 m/2.26 m	8 ft 1 in/7 ft 5 in	2.97 m/2.79 m	9 ft 9 in/9 ft 2 in	2.97 m/2.79 m	9 ft 9 in/9 ft 2 in
Outrigger footprint (l/w) (RT)	2.84 m/2.84 m	9 ft 4 in/9 ft 4 in	2.84 m/2.84 m	9 ft 4 in/9 ft 4 in	3.30 m/3.45 m	10 ft 10 in/11 ft 4 in
H Corner access*** (Standard)	48 cm	1 ft 7 in	76 cm	2 ft 6 in	69 cm	2 ft 3 in
Corner access*** (RT)	1.37 m	4 ft 6 in	1.32 m	4 ft 4 in	1.55 m	5 ft 1 in
I J Wall access front/side (Standard)	48 cm /81 cm	1 ft 7 in/2 ft 8 in	74 cm/1.07 m	2 ft 5 in/3 ft 6 in	69 cm/1.07 m	2 ft 3 in/3 ft 6 in
Wall access front/side (RT)	81 cm/1.12 m	2 ft 8 in/3 ft 8 in	74 cm/1.12 m	2 ft 5 in/3 ft 8 in	89 cm/1.40 m	2 ft 11 in/4 ft 7 in
Platform Dimensions: (l/w/h)						
Standard	69 cm/66 cm/1.14 m	27/26/44.75 in	69 cm/66 cm/1.14 m	27/26/44.75 in	69 cm/66 cm/1.14 m	27/26/44.75 in
Gated	69 cm/66 cm/1.14 m	27/26/44.75 in	69 cm/66 cm/1.14 m	27/26/44.75 in	69 cm/66 cm/1.14 m	27/26/44.75 in
Gated narrow	66 cm/51 cm/1.14 m	26/20/44.75 in	66 cm/51 cm/1.14 m	26/20/44.75 in	66 cm/51 cm/1.14 m	26/20/44.75 in
Standard fibreglass	74 cm/67 cm/1.10 m	29/26.5/43.5 in	74 cm/67 cm/1.10 m	29/26.5/43.5 in	74 cm/67 cm/1.10 m	29/26.5/43.5 in

POWER						
Power source - AC or DC models	12V DC / 110/50-60 Hz or 220/50-60 Hz AC		12V DC / 110/50-60 Hz or 220/50-60 Hz AC		12V DC / 110/50-60 Hz or 220/50-60 Hz AC	

WEIGHT						
AC models (Standard)	307 kg	677 lbs	330 kg	727 lbs	352 kg	777 lbs
AC models (RT)	299 kg	660 lbs	315 kg	694 lbs	331 kg	729 lbs
DC models (Standard)	347 kg	766 lbs	371 kg	817 lbs	393 kg	867 lbs
DC models (RT)	340 kg	749 lbs	354 kg	780 lbs	371 kg	818 lbs
Air motor (Standard)	_____	_____	_____	_____	352 kg	777 lbs
Air motor (RT)	_____	_____	_____	_____	331 kg	729 lbs

STANDARDS COMPLIANCE CE EN280, PB-10-611-03




**Sales
Rental
Service**

HELI.be

Vantegemstraat 9 | B-9230 Wetteren | +32 9 368 80 80 | info@heli.be

Specifications

MODELS	AWP™-36S		AWP™-40S	
	Metric	US	Metric	US
MEASUREMENTS				
Working height*	13.10 m	42 ft 5 in	14.28 m	46 ft 8 in
Platform height	11.10 m	36 ft 5 in	12.28 m	40 ft 2 in
A Height - stowed (Standard)	2.78 m	9 ft 1.5 in	2.78 m	9 ft 1.5 in
stowed (RT)	_____	_____	_____	_____
B tilted back** (Standard)	1.92 m	6 ft 3.5 in	1.98 m	6 ft 6 in
C Length - stowed (Standard)	1.40 m	4 ft 7 in	1.42 m	4 ft 8 in
stowed (RT)	_____	_____	_____	_____
D Length - tilted back**	2.97 m	9 ft 9 in	2.97 m	9 ft 9 in
E Width (Standard)	74 cm	2 ft 5 in	74 cm	2 ft 5 in
Width (RT)	_____	_____	_____	_____
PRODUCTIVITY				
Lift capacity	159 kg	350 lbs	136 kg	300 lbs
Indoor:				
F G Outrigger footprint (l/w) (Standard)	2.12 m/1.91 m	6 ft 11 in/6 ft 3 in	2.26 m/2.06 m	7 ft 5 in /6 ft 9 in
Outrigger footprint (l/w) (RT)	_____	_____	_____	_____
H Corner access*** (Standard)	74 cm	2 ft 5 in	79 cm	2 ft 7 in
Corner access*** (RT)	_____	_____	_____	_____
I J Wall access front/side (Standard)	36 cm/64 cm	1 ft 2 in/2 ft 1 in	38 cm/71 cm	1 ft 3 in/2 ft 4 in
Wall access front/side (RT)	_____	_____	_____	_____
Outdoor:				
F G Outrigger footprint (l/w) (Standard)	3.53 m/3.33 m	11 ft 7 in/10 ft 11 in	3.89 m /3.68 m	12 ft 9 in/12 ft 1 in
Outrigger footprint (l/w) (RT)	_____	_____	_____	_____
H Corner access*** (Standard)	1.02 m	3 ft 4 in	1.12 m	3 ft 8 in
Corner access*** (RT)	_____	_____	_____	_____
I J Wall access front/side (Standard)	1.02 m/1.32 m	3 ft 4 in/4 ft 4 in	1.12 m/1.52 m	3 ft 8 in/5 ft
Wall access front/side (RT)	_____	_____	_____	_____
Platform Dimensions: (l/w/h)				
Standard	69 cm/66 cm/1.14 m	27/26/44.75 in	69 cm/66 cm/1.14 m	27/26/44.75 in
Gated	69 cm/66 cm/1.14 m	27/26/44.75 in	69 cm/66 cm/1.14 m	27/26/44.75 in
Gated narrow	66 cm/51 cm/1.14 m	26/20/44.75 in	66 cm/51 cm/1.14 m	26/20/44.75 in
Standard fibreglass	74 cm/67 cm/1.10 m	29/26.5/43.5 in	74 cm/67 cm/1.10 m	29/26.5/43.5 in
POWER				
Power source - AC or DC models	12V DC / 110/50-60 Hz or 220/50-60 Hz AC		12V DC / 110/50-60 Hz or 220/50-60 Hz AC	
WEIGHT				
AC models (Standard)	461 kg	1,017 lbs	472 kg	1,040 lbs
AC models (RT)	_____	_____	_____	_____
DC models (Standard)	502 kg	1,107 lbs	513 kg	1,130 lbs
DC models (RT)	_____	_____	_____	_____
Air motor (Standard)	_____	_____	_____	_____
Air motor (RT)	_____	_____	_____	_____



STANDARD COMPLIANCE

CE EN280, PB-10-611-03

* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.

** Tilt back height with standard platform. For tilt back height with other platforms, please contact your sales representative.

*** Corner of platform top rail to corner of wall with ability to rotate levelling jack handle.



**Sales
Rental
Service**

HELI.be

Vantegemstraat 9 | B-9230 Wetteren | +32 9 368 80 80 | info@heli.be